



**Exterior Wall**



**COLOURLAND WEATHERFLEX PLUS** Product Code: WFP – 9000

Colourland WeatherFlex Plus Acrylic Wall Finish is a premium quality, 100% full acrylic based emulsion paint. It is specially formulated for the tropics with excellent weathering properties, fungus and algae resistance. Colourland WeatherFlex Plus Acrylic Exterior Wall finishes have excellent alkali resistance, adhesion and durability. It is formulated to provide at least 5 years protection against fungus and algae growth with correct application.

<b>Usage</b>	For decoration and protection of previously painted or new exterior walls for a long lasting aesthetic finish.
<b>Pack Size</b>	5 Lt and 20 Lt

Composition	
<b>Pigment</b>	Lightfast Non – Lead Pigments and Mineral Extenders.
<b>Binder</b>	100% Full Acrylic Emulsion.
<b>Volume Solids</b>	White 40% (Nominal), other colours will vary.
<b>Thinner / Cleaner</b>	Water.

Properties	
<b>Texture</b>	Smooth Sheen Finish.
<b>Colour</b>	A wide range of colours. Please refer Colourland Weatherflex Plus Colour Card.
<b>Theoretical Coverage</b>	11 – 13 m <sup>2</sup> /Litre.
<b>Drying Time</b>	Touch Dry, 15 – 30 min (Dependent on Temperature and Humidity). Hard Dry, 1 – 2 Hrs.
<b>Recoating Interval</b>	1 – 2 hours.

Application Method	
<b>Brush</b>	For normal use thinning is not usually necessary.
<b>Roller</b>	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
<b>Conventional Air Spray</b>	Thin with 10 – 20% by volume with water and adjust to requirement.
<b>Airless Spray</b>	Thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.

Surface Preparation	
<b>General / New</b>	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack. For best effect seal with one coat of appropriate Colourland Primer (refer to painting guide).
<b>Previously Painted</b>	Remove all loose, defective and unstable paint film or powdery residues by thorough brush and scraping. High pressure water jet is highly recommended. Treat areas effected by mould, lichens, algae and moss with Colourland Fungi Wash. Make good minor defects and cracks with suitable Colourland Exterior Brushable Crack Putty.

**Painting Guide**

Surface Condition	Primer (To Paint 1 Coat)	Finish (To Paint 2-3 Coat)
Powdery Surfaces	Colourland Hi-Performance Sealer	Colourland Weatherflex Plus
Alkaline / New Surfaces	Colourland Damp Sealer	Colourland Weatherflex Plus
Sound Surface	Colourland Wall Sealer	Colourland Weatherflex Plus
Previously Painted Surfaces	Colourland Wall Sealer	Colourland Weatherflex Plus