

Exterior Wall
COLOURLAND WEATHERFLEX ULTIMATE Product Code: WFU – XXXX


Colourland Weatherflex Ultimate is a premium pure acrylic based emulsion paint which provides 2X toughness and durability against the harsh weather. It is specially formulated with unique Heat Reflexive Technology to protect the surface from harmful UV light and Infrared Rays. This “Cool Paint” help to reflect the heat and at the same time offer a better thermal comfort environmental conditions and energy saving.

It also exhibits multifunctional properties that resist dirt pickup, chalking, flaking, mould and algae growth, which provide up to 10 years protection (with correct application). It has excellent color retention properties providing a longer lasting vibrant finish. The volatile organic compounds (VOCs) of Colourland Weatherflex Ultimate is low and contained no harmful heavy metals or toxic material. So, it is considered as an environment friendly product.

Usage	This decorative and protective emulsion paint provides a long lasting aesthetic finish to the Exterior Walls.
Pack Size	1 Lt and 5 Lt

Composition	
Pigment	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	100% Full Acrylic Emulsion.
Volume Solids	White 38% (Nominal), other colours will vary.
Thinner / Cleaner	Water.

Properties	
Texture	Smooth Sheen Finish.
Colour	A wide range of colours. Please refer Colourland Weatherflex Ultimate Colour Card.
Theoretical Coverage	11 – 13 m ² /Litre.
Drying Time	Touch Dry, 15 – 30 min (Dependent on Temperature and Humidity). Hard Dry, 1 – 2 Hrs.
Recoating Interval	1 – 2 hours.

Application Method	
Brush	For normal use thinning is not usually necessary.
Roller	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	Thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.

Surface Preparation	
General / New	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack. For best effect seal with one coat of appropriate Colourland Primer (refer to painting guide).
Previously Painted	Remove all loose, defective and unstable paint film or powdery residues by thorough brush and scraping. High pressure water jet is highly recommended. Treat areas effected by mould, lichens, algae and moss with Colourland Fungi Wash. Make good minor defects and cracks with suitable Colourland Exterior Brushable Crack Putty.

Painting Guide

Surface Condition	Primer (To Paint 1 Coat)	Finish (To Paint 2-3 Coat)
Powdery Surfaces	Colourland Hi-Performance Sealer	Colourland Weatherflex Ultimate
Alkaline / New Surfaces	Colourland Damp Sealer	Colourland Weatherflex Ultimate
Sound Surface	Colourland Wall Sealer	Colourland Weatherflex Ultimate
Previously Painted Surfaces	Colourland Wall Sealer	Colourland Weatherflex Ultimate