



Roof



COLOURLAND ROOFLEX ACRYLIC MID SHEEN ROOF FINISH

Product Code: RF – 9XXX

Rooflex Acrylic Mid Sheen Roof Finish is a premium quality, highly durable, 100% acrylic based emulsion paint. It is specially formulated for the tropic roofings with excellent weathering properties, fungus and algae resistance. Highly recommended for old and new roof such as unglazed roof tiles, cement roof tiles and cement fibre roofing sheet. Colourland Rooflex is Environment Friendly, non-lead and non-mercury. Incorporated with excellent light fast pigment with high mould and alkali resistance.

Usage	For decoration and protection of roof tiles, block water seepage on old roof-tiles. Can also be painted on exterior cement and cement fibre structure. Rooflex excellent light fast pigment with high mould and alkali resistant formulation will provide a durable long lasting aesthetic finish.
Pack Size	5 Lt

Composition	
Pigment	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	100% Full Acrylic Emulsion.
Volume Solids	White 40% (Nominal)
Thinner / Cleaner	Water.

Properties	
Texture	Smooth Sheen Finish.
Colour	Ranges of colours. Please refer Colourland Rooflex Colour Card.
Theoretical Coverage	11 – 13 m ² /Litre.
Drying Time	Touch Dry, 15 – 30 min (Dependent on Temperature and Humidity). Hard Dry, 1 – 2 Hrs.
Recoating Interval	1 – 2 hours.

Application Method	
Brush	For normal use thinning is not usually necessary.
Roller	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	Thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.

Surface Preparation	
General / New	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack. For best effect seal with one coat of appropriate Colourland Primer (refer to painting guide).
Previously Painted	Remove all loose, defective and unstable paint film or powdery residues by thorough brush and scraping. High pressure water jet is highly recommended. Treat areas effected by mould, lichens, algae and moss with Colourland Fungi Wash. Make good minor defects and cracks with suitable Exterior Grade Filler.

Painting Guide

Surface Condition	Primer (To Paint 1 Coat)	Finish (To Paint 2-3 Coat)
Powdery Surfaces	Colourland Hi-Performance Sealer	Colourland Rooflex
Alkaline / New Surfaces	Colourland Damp Sealer	Colourland Rooflex
Sound Surface	Colourland Wall Sealer	Colourland Rooflex
Previously Painted Surfaces	Colourland Wall Sealer	Colourland Rooflex