



Interior Wall



COLOURLAND ORIGINAL PLASMA ION CEILING Product Code: OPI 9102

Colourland Original Plasma Ion Ceiling is specially developed with Latest Paint Technology into a LOW VOC and LOW ODOUR latex emulsion paint provides care for whole family by Continuous Unlimited Negative Ion Emission for Healthy Living Environment. Its Continuous Negative Ion Emitting features will attack airborne particles like Bacteria, Fungus & Mould Spores, Pollens, Dirts and Mites. Killing and rendering them in-active even while you are sleeping, providing for a Clean Air Environment Living. Children and Adults will have less Asmathic as well as other Air Borne diseases attack. It provide Smooth Soft Matt Finishes that is able to enhance the ceiling luxurious ambient while protecting them at the same time. It is fungus resistant and formulated for a long lasting ceiling finishing.

Usage	For decoration and protection of wall, ceiling, plaster, brickwork and cement board, hard and soft board.
Pack Size	5 Lt and 20 Lt

Composition	
Pigment	Lightfast Non – Lead Pigments and Mineral Extenders.
Binder	Acrylic Emulsion
Volume Solids	White 45% (Nominal)
Thinner / Cleaner	Water.

Properties	
Texture	Soft Matt Finish
Colour	White Colour Only.
Theoretical Coverage	10 – 12 m ² /Litre.
Drying Time	Touch Dry 15 – 30 min (Dependent on Temperature and Humidity).
Recoating Interval	1 – 2 hours.

Application Method	
Brush	For normal use thinning is not usually necessary.
Roller	For normal use thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.
Conventional Air Spray	Thin with 10 – 20% by volume with water and adjust to requirement.
Airless Spray	Thinning is not usually necessary. Can be thin 5 – 10% by volume with water to assist application.

Surface Preparation	
General / New	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax. To have better finish rubbed down surface using suitable abrasive and dust off. If after thorough preparation surface remain powdery, or suffer from alkali attack. For best effect seal with one coat of appropriate Colourland Primer (refer to painting guide).
Previously Painted	Remove all loose, defective and unstable paint film or powdery residues by thorough brushing and scraping. Make good minor defects and cracks with suitable grade filler.

Painting Guide		
Surface Condition	Primer (To Paint 1 Coat)	Finish (To Paint 2-3 Coat)
Powdery Surfaces	Colourland Hi-Performance Sealer	Colourland Original Plasma Ion Ceiling
Alkaline / New Surfaces	Colourland Damp Sealer	Colourland Original Plasma Ion Ceiling
Sound Surface	Colourland Wall Sealer	Colourland Original Plasma Ion Ceiling
Previously Painted Surfaces	Colourland Wall Sealer	Colourland Original Plasma Ion Ceiling